ZHIGUANG

Zhiguang Digital All-Liquid Cooling Industrial and Commercial Energy Storage System (110kW/233kWh)

www.gzzg.com

Features

- Ultimate modularity and standardized design
- PACK and PCS dual channel liquid cooling
- Flexible layout combination, [illegible] foot combination 3.13 megawatt hours
- BMS、PACK、Cabinet, three-level [illegible] warning
- Battery, PACK, and cabinet three-level [illegible]
- Networked, EMS energy management, and cloud based big data lifecycle management based on the 5S fully digital concept

Basic	
Configuration	IP260S
Number of Packs	5
Short-circuit current	12.2kA
Electrical	
Rated charging current	160A
Max. Charging Current	160A, lasts 1minute
Nominal Capacity	232kWh
Voltage Range	728~949V
Nominal Voltage	832V
Max. continuous current	140A
Rated Power	100kW(0.5P)
Auxiliary Power	
Cooling Unit Power	Cooling:2kW
Voltage range	176-264VAC
BMS Power	60W
System	
Anticorossion	C5
IP rating	Battery:IP66,Control:IP65,NEMA 4X
Power connection	Fast Plug
Grounding Mode	≥4㎡, Meet the Local Cable Requirements
Cooling Mode	Liquid Cooling
Storage Environment Temperature	-40~60℃
Operating Environment Temperature	-25 ~55 ℃
Environment Humidity	RH≤95% (Non-Condensing)
Altitude Requirements	< 4000m(> 3000m Derating)
Dimension	1500*1300*2208mm
Weight	3000kg
Color	RAL7035
PCS	
Basic	
Rated Power	100kVA
Overload Capability	Constant Operation@110%, 1min@120%
Efficiency	99%
Power Response time	< 20ms
Charge/Discharge Switching Time	<50ms
Operating Environment Temperature	-40 ~ +60℃(>50℃ Derating)
Installation	wall Mounted
IP rating	IP66
Cooling Mode	Liquid Cooling
Isolation Method	Non-Isolated
DC side	
Max. Voltage	1000V
Operating Voltage Range	600~1000V
Full Load Operating Voltage Range	600 ~ 1000V
AC side	
Rated Voltage	380V
Rated Current	145A
Max. Long-Term Operating Current	152A
Voltage Range	±15%
Frequency	50/60Hz±5Hz
Total Current Harmonics	< 3%
Communication	
Communication Interface	1xRS485+2xEthernet
Communications Protocol	Modbus-RTU/Modbus-TCP

Add: No. 89, Ruihe Road, Huangpu District, Guangzhou, China
Tel: 020-83909333
Fax: 020-83909222
Web: www.gzzg.com